

TRANSCUBE GLOBAL 132-1,204 US GALLONS



The TransCube Global is a transportable, environmentally friendly double-walled fuel storage tank, that offers an efficient solution for on-site fueling and auxiliary supply.

With its fully transportable design and ability to fuel multiple pieces of equipment simultaneously, the TransCube will save you time and double or triple the run times of your equipment.

FEATURES

LOCKABLE EQUIPMENT CABINET

Equipment and ports are secure and spills are contained. Secure hose access enables fueling while cabinet is locked.

CORNER BRACKETS

Liftable by crane and easily stackable: two high full and three high empty.

GALVANIZED FRAME

Strong, durable and secure structure with added protection from bumps and scratches.

DOUBLE WALLED 110% CONTAINMENT

Built-in, weatherproof secondary containment eliminates the need for pans or basins.

REMOVABLE INNER TANK

For routine cleaning, maintenance and inspection.

INTERNAL BAFFLES

Designed to maximize stability when handling the tank full of fuel.

FOUR WAY FORKLIFT POCKETS

Quick and easy maneuvering and mobility.





IDEAL USES AND APPLICATIONS

ONSITE FUEL SUPPLY

Easily refuel machinery on site when needed and cut back on fuel delivery waiting times.

FUEL TRANSPORT

Meeting multiple worldwide transport regulations, the TransCube can transport fuel safely anywhere you need it.

GENERATOR AND AUXILIARY EQUIPMENT

TransCube fuel tanks have the ability to quickly and efficiently connect to three diesel powered pieces of equipment and refuel equipment via pump at the same time.

MODELS AND CAPABILITIES



SPECIFICATIONS	05TCG	10TCG	20TCG	30TCG	40TCG	50TCG
Capacity (Nominal / safe fill (95%))	132/ 125 US Gallons	251/ 238 US Gallons	552/525 US Gallons	787/ 748 US Gallons	1,000/ 950 US Gallons	1,204/ 1,144 US Gallons
Dimensions (L x W x H)	45 x 45 x 34 in	45 x 45 x 52 in	90 x 45 x 52 in	90 x 61 x 52 in	91 x 91 x 45 in	91 x 91 x 52 in
Weight (empty / full)	915 / 1,960 lbs	1,190 / 3,178 lbs	1,814 / 6,194 lbs	2,425 / 8,666 lbs	3,483 / 11,411 lbs	3,703 / 14,550 lbs
Design approvals	UL142, CAN/ULC-S601, US DOT, UN-IBC, TRANSPORT CANADA, NFPA30					

